



Product Details :-

Code : CLB1260
Model : Panel light bottom opening type
Series : Clean room

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 60 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current
Power factor corrected
Driver registration No : BIS-IS15885-2-13:2012
R-63000353
& IS 16104:2012

Driver Efficiency : > 85%


Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >80lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI (Ra) : Typical 80
Diffuser : Polycarbonate diffuser
LED Life Span : 50,000 burning hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP54

Light distribution:-



\* On all electrical parameters (+/-10%) tolerance to be considered

\* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



\* Customized dimensions can supply on request

Physical Details :-

Material & Construction : CRCA enclosure
Fixture dimensions : L 325mm x W 615mm x H 50mm
Cut out dimensions : L 285mm x W 572mm(With I & L Clamps)
Mounting type : Recess mount with clamps

Protections :-

Output Over voltage / protected : Complied
Output Over current and Short circuit : Complied
Surge protection : Inbuilt driver 4KV, External 5KV

Applications : Indoor & Clean room applications

