



Product Details :-

Code : LHWB03.560
Model : Linear Highbay

Electrical Data :-

Workig voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 60 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver Efficiency : > 85%


Light Data :-

LED details : SMD LED, LM80 certified
System efficacy : >100lm/W
Beam angle : 80Deg
Lens : Polycarbonate lens
Glass : Toughened glass
CCT range : 2700-6500K
CRI(Ra) : Typical 70
LED Life time : 50,000 burning hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP65

Light distribution:-



Physical Details :-


Material : Aluminum
Construction : Extruded aluminum enclosure
Fixture dimensions : L 510mm x W 70mm x H 75mm
Weight : 1.8 Kgs approx.,
Mounting type : Surface mount

Protections :-

Output Over voltage / Under voltage protected : Provided
Output Over current and Short circuit : Provided
Surge protection : Inbuilt driver 4KV

Applications : Indoor, Outdoor & Commercial

AAI curve :-



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice