



Product Details :-

Code : LC6R/11
Model : COB light

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 6 Watt
Power factor : > 0.9
Frequency : 50/60 Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver efficiency : > 85%


Light Data :-

LED Make : COB LED, LM80 certified
System efficacy : >60lm/W
Beam angle : 42°
CCT range : 2700 - 6500K
CRI(Ra) : Typical 70
Reflector : Polycarbonate reflector
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP20

Light Distribution :-



0
Maintenance

50%
ENERGY SAVING

ZERO
Mercury

Physical Details :-

Material & construction : Pressure die cast aluminum enclosure
Fixture Dimensions : Dia 40mm x H 63mm
Cut out Dimensions : Dia 33 mm
Suitable fixing : Flase ceiling

Applications

: **Indoor & commercial**

* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

