



**Product Details :-**

Code : LSR1  
Model : Spot Light

**Electrical Data :-**

Input voltage range : 140 - 240VAC  
Power : 1 Watt  
Frequency : 50 Hz  
THD : < 15%  
Driver : Constant current

**Light Data :-**

LED Type : SMD LED, LM80 Certified  
LED efficacy : >120lm/W  
Beam angle options : 15,24,36,42&60Deg  
CCT range : 2700 - 6500K  
CRI (Ra) : Typical 70  
Reflector : Polycarbonate reflector  
LED Life time : 50,000 hours

**Environmental :-**

Working temperature : 0°C to + 55 °C  
Working humidity : 10 to 90% RH  
Storage temperature : -10 °C to + 85 °C  
IP rating : IP 20

**Physical Details :-**

Material & Construction : Pressure die cast aluminum casing  
Fixture Dimensions : 35mm Dia x 50mm H  
Cut out Dimensions : 32 mm Dia  
Type of mounting : False ceiling

**Applications : Indoor & Commercial lighting**



**0**  
Maintenance



**ZERO**  
Mercury

\* On all electrical parameters (+/-10%) tolerance to be considered

\* On all mechanical dimensions & weight (+/-5%) tolerance to be considered



Note : The above specification are subjected to change without prior notice

VER3.24