



Product Details :-

Code : HLD1928
Model : Surface cob light - HLD series

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 8 Watt
Power factor : >0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver efficiency : > 85%



Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >80lm/W
Beam angle : 24 Deg
CCT range : 2700 - 6500K, Multi CCT
CRI(Ra) : Typical 70
Lens : Polycarbonate lens
LED Life time : 50,000 hours

Physical Details :-

Material & Construction : Pressure die cast aluminum
Fixture dimensions : Dia 85mm x H 104mm
Weight : 0.36 Kgs
Suitable fixing : Surface mount


Applications

: Indoor & Commercial lighting


Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP20

Light distribution:-



AAI Curve:-



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice