



Product Details :-

Code : HLD412
Model : COB light - HLD series

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 15 Watt
Power factor : >0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver efficiency : > 85%



Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >75lm/W
Beam angle : 60 Deg
CCT range : 2700 - 6500K
CRI(Ra) : Typical 70
Diffuser : Polycarbonate diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP20

Light distribution:-




Physical Details :-

Material & Construction : Pressure die cast aluminum
Fixture dimensions : Dia 108mm x H 65mm
Cut out dimensions : Dia 92mm
Weight : 0.38 Kgs
Suitable fixing : False ceiling

Applications : Indoor & Commercial lighting

AAI Curve:-



* On all electrical parameters (+/-10%) tolerance to be considered
* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice