



FortuneArrrt LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearrt.com

Product Technical specification

FA-F/DD-PS 1675

Product Details :-

Code : LFLF20S24A
Model : Flood light With SMD

Electrical Data :-

Input voltage : 24 VAC
Power : 20 Watt
Driver : Contant current

Light Data :-

LED Type : SMD LED, LM80 Certified
System Efficacy : > 90 lm/Watt
Beam angle : 120Deg
CCT range : 2700 - 6500K
CRI : Typical 80
Glass : Toughened glass
Reflector : Polycarbonate reflector
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP65

Physical Details :-

Material : LM6 grade aluminum or higher grade
Product finish : Powder coated and water proof
Construction : Pressure die cast aluminum enclosure
Fixture Dimensions : L 184mm x W 154mm x H 45mm
Weight : 0.8 Kgs approx.,
Mounting type : Wall /Pole/ Suspension mount

Applications : Indoor, Outdoor & Industrial



0
Maintenance

50%
ENERGY
SAVING

ZERO
Mercury



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

VER2.24