



Product Details :-

Code : LST36K
Model : Street light

Electrical Data :-

Working voltage range : 100 - 277 VAC
Input voltage : 220 - 240 VAC
Power : 36W
Power factor : >0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver registration No. : BIS-IS15885-2-13:2012,
R-63000353
IS 16104:2012
Driver Efficiency : > 85%


Light Data :-

LED : SMD LED, LM80 Certified
System efficacy : >120 Lm/W
Beam angle : Batwing distribution
CCT range : 2700 - 6500K
CRI (Ra) : Typical 80
Secondary Optics : Polycarbonate LENS cover
Life span : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP66

Light Distribution :-



0
Maintenance

50%
ENERGY
SAVING

ZERO
Mercury

Physical Details :-

Material & Construction : Pressure die cast aluminum enclosure
Product finish : Powder coated
Fixture Dimensions : L 290mm x W 120mm x H 65mm
Suitable pole diameter : 40-45mm dia

Protections :-

Output Over voltage /
Under voltage protected : Provided
Output Over current and
Short circuit : Provided
Surge protection : With stand upto 4KV

Applications : Outdoor, Industrial

* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

VER1.25

