



FortuneArtrt LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearttrt.com

Product Technical specification

FA-F/DD-PS 2124

Product Details :-

Code : PPBK5080440
Model : Linear profile light - Surface

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 40 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 10%
Driver : Constant current and active power factor corrected
Driver efficiency : > 85%



Light Data :-

LED Type : SMD LED, LM80 Certified
Beam angle : Lambertian distribution
CCT range : 2700K - 6500K
CRI : Typical 80
Diffuser : Polycarbonate diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP20

Light distribution:-



Physical Details :-

Material & Construction : CC extrusion with black finish
Fixture Dimensions : L 1205mm x W 50mm x H 80mm
Mounting type : Suitable for Surface & Hanging

Applications

: Indoor & Commercial

* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



VER1.25