



FortuneArtr LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearttr.com

Product Technical specification

FA-F/DD-PS 2265

Product Details :-

Code : LCSIPAW20
Model : Surface Cob light

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 20 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver efficiency : > 85%


Light Data :-

LED Type : COB LED, LM80 Certified
System efficacy : >80 Lm/W
Beam angle : 36°
CCT range : 2700 - 6500K
CRI (Ra) : Typical 70
Lens : Polycarbonate lens
Trim color : Black
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : 0°C to + 85 °C
IP rating : IP 65

Light distribution:-



Physical Details :-

Material & Construction : Extruded aluminum enclosure
Casing color : White powder coated
Fixture Dimensions : Dia 94mm x H 135mm
Suitable fixing : Surface mount

Applications : Indoor, Outdoor & Commercial

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

* On all electrical parameters (+/-10%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



VER1.25