



Product Details :-

Code : CAC611
Model : COB light - CAC series

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 7 Watt
Power factor : >0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver efficiency : > 85%

Light Data :-

LED Type : COB, LM80 Certified
System efficacy : >70 Lm/W
Beam angle : 36 Deg
CCT range : 2700 - 6500K
CRI(Ra) : Typical 80
Reflector : Polycarbonate reflector
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP20




Physical Details :-

Material & Construction : Pressure die cast aluminum
Fixture dimensions : Dia 63mm x H 63mm
Cut out dimensions : Dia 54mm
Suitable fixing : False ceiling
Available casing colours : White & Black
Available reflector colours : Gold, Black, Rose gold & silver

Applications

: Indoor & Commercial lighting

Light distribution:-



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice