FortuneArrt LED Lighting Pvt Ltd.,
WQ : Survey no:509/1/2, Apparel Export park,
Gundlapochampally, Hyderabad - 500014
Web : www.fortunearrt.com

Product Technical specification

FA-F/DD-PS 1154

Product Details :-

Code	: HLD672
Model	: COB light - HLD series

Electrical Data :-

Working voltage range	: 100 - 277VAC
Input voltage	: 220 - 240VAC
Power	: 18 Watt
Power factor	: > 0.95
Frequency	: 50Hz
THD	: < 15%
Driver	: Constant current active Powerfactor corrected
Driver efficiency	: > 85%

Light Data :-

LED Type	: COB, LM80 Certified
System efficacy	: > 80 Lm/W
Beam angle	: 36 Deg
CCT range	: 2700 - 6500K
CRI(Ra)	: Typical 70
Secondary optics	: Polycarbonate lens
LED Life time	: 50,000 hours

Environmental :-

Working temperature	: 0°C to + 55 °C
Working humidity	: 10 to 90% RH
Storage temperature	: -10 °C to + 85 °C
IP rating	: IP20

0 Maintenance

50% ENERGY SAVING

ZERO Mercury

Physical Details :-

Material & Construction	: Pressure die cast aluminum casing
Fixture dimensions	: Dia 84mm x H 110mm
Cut out dimensions	: Dia 74mm
Suitable fixing	: False ceiling

Applications : Indoor & Commercial lighting

Light distribution:-



*** On all electrical parameters (+/-10%) tolerance to be considered**

*** On all mechanical dimensions & weight (+/-5%) tolerance to be considered**

Note : The above specification are subjected to change without prior notice

VER2.26