



**Product Details :-**

Code : LCSW30/8  
Model : Surface Coblight

**Electrical Data :-**

Working voltage range : 100 - 277 VAC  
Input voltage : 220 - 240 VAC  
Power : 30Watt  
Power factor : > 0.9  
Frequency : 50Hz  
THD : < 15%  
Driver : Constant current active  
Powerfactor corrected  
Driver Efficiency : > 85%


**Light Data :-**

LED Type : COB, LM80 Certified  
System efficacy : >80Lm/W  
Beam angle : 36°  
CCT range : 2700-6500K  
CRI : Typical 70  
Secondary optics : Polycarbonate LENS  
LED Life time : 50,000 hours

**Environmental :-**

Working temperature : 0°C to + 55 °C  
Working humidity : 10 to 90% RH  
Storage temperature : -10°C to + 85 °C  
IP rating : IP20

**Light distribution :**



\* On all electrical parameters (+/-10%) tolerance to be considered

\* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



**0**  
Maintenance

**50%**  
ENERGY  
SAVING

**ZERO**  
Mercury

**Physical Details :-**

Material : Extruded aluminum enclosure  
Product finish : White powder coated  
Fixture Dimensions : Dia 80mm x H 165mm  
Suitable mounting : Surface mount

**Applications : Indoor,Outdoor & Commercial lighting**

