



**Product Details :-**

Code : LCZ15/R/2  
Model : Zoom cob light

**Electrical Data :-**

Working voltage range : 100 - 277VAC  
Input voltage : 220 - 240VAC  
Power : 15 Watt  
Power factor : > 0.9  
Frequency : 50 Hz  
THD : < 15%  
Driver : Constant current active  
Powerfactor corrected  
Driver efficiency : > 85%


**Light Data :-**

LED Make : COB LED, LM80 certified  
System efficacy : >80Lm/W  
Beam angle : 24°  
CCT range : 2700 - 6500K  
CRI (Ra) : Typical 70  
Reflector : Polycarbonate reflector  
LED Life time : 50,000 hours

**Environmental :-**

Working temperature : 0°C to + 55 °C  
Working humidity : 10 to 90% RH  
Storage temperature : -10 °C to + 85 °C  
IP rating : IP20

**Light Distribution :-**



**Physical Details :-**

Material & construction : Pressure die cast aluminum enclosure  
Fixture Dimensions : Dia 110mm x H 72mm  
Cut out Diameter : Dia 102mm  
Suitable fixing : Flase ceiling

**Applications : Indoor & commercial**

\* On all electrical parameters (+/-10%) tolerance to be considered

\* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

