



FortuneArtrt LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,
Gundlapochampally, Hyderabad - 500014
Web : www.fortunearttrt.com

Product Technical specification

FA-F/DD-PS 1062

Product Details :-

Code : CLTSS1470
Model : Top opening Panel light SS top frame
Series : Clean room

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 70 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current
Power factor corrected
Driver registration No : BIS-IS15885-2-13:2012
R-63000353
& IS 16104:2012
Driver Efficiency : > 85%


Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >80 Lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI (Ra) : Typical 80
Diffuser : Polycarbonate diffuser
LED Life Span : 50,000 burning hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP54

Light distribution :-



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



0
Maintenance

50%
ENERGY
SAVING

ZERO
Mercury

* Customized dimensions can supply on request

Physical Details :-

Material & Construction : CRCA enclosure & SS top frame
Fixture dimensions : L 310mm x W 1200mm x H 60mm
Cut out dimensions : L 285mm x W 1180mm(With I & L Clamps)
Mounting type : Recess mount with clamps

Protections :-

Output Over voltage /
protected : Complied
Output Over current and
Short circuit : Complied

Surge protection : Inbuilt driver 4KV,
External 10KV

Applications : Indoor & Clean room applications



VER2.23