



Product Details :-

Code : DL0224
Model : Down light

Electrical Data :-

Working voltage range : 120 - 265VAC
Input voltage : 220 - 240VAC
Power : 24 watt
Frequency : 50Hz
Driver : Constant current

Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >100 Lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI (Ra) : Typical 80
Diffuser : Polycarbonate diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP20




Physical Details :-

Material : LM6 grade aluminum or higher grade
Product finish : Powder coated
Construction : Pressure die cast aluminum enclosure
Fixture Dimensions : L 155mm x W 155mm x H 52mm
Fixture cut-out diameter : 135mm x 135mm
Suitable fixing : False ceiling

Applications

: Indoor & Commercial

Light Distribution :-



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

VER4.26