



## FortuneArtrr LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : [www.fortunearttr.com](http://www.fortunearttr.com)

## Product Technical specification

FA-F/DD-PS 1448

### Product Details :-

Code : DL1125  
Model : PC Model - DOB

### Electrical Data :-

Working voltage range : 140 - 277VAC  
Input voltage : 220 - 240VAC  
Power : 25 Watt

### Light Data :-

LED Type : SMD LED, LM80 Certified  
System efficacy : >60lm/W  
Beam angle : 120°  
CCT range : 2700 - 6500K  
CRI(Ra) : Typical 80  
Diffuser : Polycarbonate diffuser  
LED Life time : 50,000 hours

### Environmental :-

Working temperature : 0°C to + 55 °C  
Working humidity : 10 to 90% RH  
Storage temperature : -10 °C to + 85 °C  
IP rating : IP20

### Physical Details :-

Material & Construction : Polycarbonate casing  
Fixture Dimensions : Dia 160mm x H 30mm  
Suitable ceiling cut out : Dia 140mm  
Suitable fixing : False ceiling

**Applications : Indoor & commercial**



**0**  
Maintenance



\* On all electrical parameters (+/-10%) tolerance to be considered

\* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



**VER3.26**