



FortuneArtr LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,
Gundlapochampally, Hyderabad - 500014
Web : www.fortunearttr.com

Product Technical specification

FA-F/DD-PS 1446

Product Details :-

Code : DL117
Model : PC Model - DOB

Electrical Data :-

Working voltage range : 140 - 277VAC
Input voltage : 220 - 240VAC
Power : 7 Watt

Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >60 Lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI(Ra) : Typical 80
Diffuser : Polycarbonate diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP20

Physical Details :-

Material & Construction : Polycarbonate casing
Fixture dimensions : Dia 95mm x H 35mm
Suitable ceiling cut out : Dia 70mm
Suitable fixing : False ceiling

Applications : Indoor & commercial



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered



Note : The above specification are subjected to change without prior notice

VER3.26