



FortuneArtr LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearttr.com

Product Technical specification

FA-F/DD-PS 3025

Product Details :-

Code : EMBH24W
Model : Emergency Bulk Head

Electrical Data :-

Working voltage range : 90 - 265 VAC
Power : 24 Watt
Driver : DOB
Battery type : Lithium ion battery
Emergency power : 3W
Charging time : 4 hours
Backup time : 3 - 4 hours

Light Data :-

LED Type : SMD LED, LM80 Certified
Beam angle : 120°
CCT range : Cool White
Diffuser : Polycarbonate diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0 °C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP20

Physical Details :-

Material & Construction : Polycarbonate casing
Fixture Dimensions : L 206mm x W 100mm x H 58mm
Suitable fixing : Surface mount

Applications : Indoor & Commercial



0
Maintenance



ZERO
Mercury

Note : The above specification are subjected to change without prior notice



VER1.26