



Product Details :-

Code : FLJA30S
Model : Flood light With SMD


Electrical Data :-

Input voltage range : 100 - 277 VAC
Input voltage : 220 - 240 VAC
Power : 30 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver registration No : BIS-IS15885-2-13:2012
R-63000353
& IS 16104 : 2012
Driver Efficiency : > 85%

Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >100Lm/W
Beam angle : 120 °
CCT range : 2700 - 6500K, R, G, B, RGB
CRI(Ra) : Typical 80
Glass : Toughened glass
Reflector : Polycarbonate reflector
LED Life time : 50,000 hours

Light Distribution :-



Physical Details :-

Material : LM6 grade aluminum or higher grade
Product finish : Powder coated and water proof
Construction : Pressure die cast aluminum enclosure
Fixture dimensions : L 184mm x W 154mm x H 45mm
Mounting type : Wall / Surface/Suspension mount

Environmental :-

Working temperature : 0 °C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP65

Protections :-

Output Over voltage /
Under voltage protected : Provided
Output Over current and
Short circuit : Provided
Surge protection : Withstand upto 4KV

Applications : Indoor, Outdoor & Industrial

* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

