



Product Details :-

Code : LHBF150
Model : Dome high bay - SMD & Fin Model

Electrical Data :-

Working voltage range : 100 - 277 VAC
Input voltage : 220 - 240 VAC
Power : 150Watt
Power factor : >0.95
Frequency : 50Hz
THD : < 10%
Driver : Constant current active
Powerfactor corrected
Driver registration No : BIS-IS15885-2-13:2012
R-63000353
& IS 16104:2012
Driver efficacy : > 85%

Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >100 Lm/W
Beam angle : 90°
CCT range : 2700 - 6500K
CRI(Ra) : Typical 80
Diffuser : Polycarbonate clear diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0 °C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP54



Physical Details :-


Material : Aluminum
Construction : fabricated aluminum casing
Fixture Dimensions : Dia 430mm x H 380mm
Weight : 3.1 Kgs apprx.,
Suitable fixing : Suspension

Protections :-

Output Over voltage /
Under voltage protected : Provided
Output Over current and
Short circuit : Provided
Surge protection : Inbuilt driver 4KV,
External 10KV

Applications : Indoor, Outdoor & Industrial

Light distribution :



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

