



Product Details :-

Code : LST70J3
Model : Street light

Electrical Data :-

Working voltage range : 100 - 277 VAC
Input voltage : 220 - 240 VAC
Power : 70W
Power factor : >0.95
Frequency : 50 Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected

Driver registration No. : BIS-IS15885-2-13:2012,
R-63000353
& IS 16104 : 2012

Driver Efficiency : > 85%


Light Data :-

LED : SMD LED, LM80 Certified
System efficacy : >120Lm/W
Beam angle : Batwing distribution
CCT range : 2700 - 6500K
CRI(Ra) : Typical 80
Secondary Optics : Polycarbonate LENS cover
Life span : 50,000 hours

Environmental :-

Working temperature : 0 °C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP66

Light distribution :-



0
Maintenance

50%
ENERGY
SAVING

ZERO
Mercury

Physical Details :-

Material & Construction : Pressure die cast aluminum enclosure
Product finish : Powder coated
Fixture Dimensions : L 400mm x W 140mm x H 50mm
Suitable pole diameter : 40-45mm dia

Protections :-

Output Over voltage /
Under voltage protected : Provided
Output Over current and
Short circuit : Provided
Surge protection : Inbuilt driver 4KV,
External 10KV

Applications

: Outdoor, Industrial /Commercial

* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

VER 6.24