



FortuneArtrt LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,
Gundlapochampally, Hyderabad - 500014
Web : www.fortunearttrt.com

Product Technical Specification

FA-F/DD-PS 2220

Product Details :-

Code : PANS1118WC
Model : Panel light
Series : Recess Panel light

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 18 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Power factor corrected
Driver Efficiency : > 85%

Light Data :-

LED Type : SMD LED, LM80 certified
System efficacy : >80 Lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI(Ra) : Typical 80
Diffuser : Polycarbonate diffuser
LED Life Span : 50,000 burning hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP20



0
Maintenance




Physical Details :-

Material & construction : CRCA body
Product finish : Powder coated
Fixture Dimensions : L 295mm x W 295mm x H 36mm
Cut out dimensions : L 278mm x W 278mm
Mounting type : Recess mount

Applications

: Indoor & Commercial

Light Distribution :-



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



VER2.26