



Product Details :-

Code : UFO100
Series : UFO - Die cast

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 100 Watt
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver registration No : BIS-IS15885-2-13:2012
R-63000353
& IS 16104:2012
Driver efficiency : > 85%



Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >100 Lm/W
Beam angle : 90°
CCT range : 2700 - 6500K
CRI (Ra) : Typical 80
Secondary Optics : Polycarbonate LENS cover
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP65

Light distribution :-



0 Maintenance



Physical Details :-

Material & Construction : Pressure die cast aluminum with powder coated
Fixture Dimensions : Dia 310mm x H 160mm
Weight : 2.7 Kgs approx.,
Suitable fixing : Suspension / Ceiling mount

Protections :-

Output Over voltage / Under voltage protected : Provided
Output Over current and Short circuit : Provided
Surge protection : Inbuilt driver upto 4KV, External 10KV surge

Applications : Indoor, Outdoor & Cold room areas



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered