



Product Details :-

Code : XDESB6
Model : Edge Surface dome - round

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 6 Watt
Power factor : >0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver efficiency : > 85%

Light Data :-

LED Type : SMD LED, LM80 certified
System efficacy : >70 Lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI (Ra) : Typical 80
Diffuser : Polycarbonate diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP20



Special features

- * Slimmer range in this series
- * Edge lit technology
- * Optics comprise of
PMMA light guide plate(LGP) + Diffuser + Reflector


Physical Details :-

Material : LM6 grade or higher grade
Product finish : Black Powder coated
Construction : Pressure die cast aluminum enclosure
Fixture Dimensions : Dia 118mm x H 32mm
Suitable fixing : Surface mount

Applications

: Indoor, Outdoor & Commercial

Light Distribution :-



* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

VER3.26