



FortuneArtr LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearttr.com

Product Technical Specification

FA-F/DD-PS 3040

Product Details :-

Code : WLPK13
Model : Wall light

Electrical Data :-

Working voltage range : 100 - 277 VAC
Input voltage : 220 - 240 VAC
Power : 3 Watt
Power factor : >0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current

Light Data :-

LED Type : COB, LM80 certified
CCT range : 2700 - 6500K
CRI(Ra) : Typical 70
Reflector : Polycarbonate reflector
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0 °C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : 0 °C to + 85 °C
IP rating : IP65

Physical Details :-

Material & Construction : Polycarbonate casing
Dimensions : L 78mm x W 70mm x H 61mm
Type of mounting : Wall mount

Applications : Commercial / Architecture lighting



0
Maintenance



* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

* On all electrical parameters (+/-10%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

VER1.26