



FortuneArtrr LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearttr.com

Product Technical Specification

FA-F/DD-PS 3032

Product Details :-

Code : WWIPA150RGB

Model : Wall washer

Electrical Data :-

Working voltage range : 100 - 277VAC

Input voltage : 220 - 240VAC

Power : 50 Watt

Frequency : 50Hz

Driver : Constant current



Light Data :-

LED details : SMD LED, LM80 certified

Beam angle : 36Deg (Other beam options on request)

Secondary Optics / LENS : Polycarbonate lens

CCT range : RGB

LED Life time : 50,000 burning hours

Environmental :-

Working temperature : 0 °C to + 55 °C

Working humidity : 10 to 90% RH

Storage temperature : -10 °C to + 85 °C

IP rating : IP66

Physical Details :-

Material : Aluminum

Construction : Extruded aluminum enclosure

Fixture dimensions : L 987mm x W 50mm x H 55mm

Weight : 1.8 Kgs approx.,

Mounting type : Surface mount

Applications : Outdoor & Commercial lighting

* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



VER 1.26