



FortuneArtr LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearttr.com

Product Technical Specification

FA-F/DD-PS 1390

Product Details :-

Code : WWIPAV136
Model : Wall washer with Visor

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 36 Watt
Power factor : > 0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver Efficiency : > 85%


Light Data :-

LED details : SMD LED, LM80 certified
System efficacy : >70 Lm/W
Beam angle : 24, 36Deg (Other beam options on request)
Secondary Optics / LENS : Polycarbonate lens
CCT range : 2700-6500K
CRI(Ra) : Typical 70
LED Life time : 50,000 burning hours

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP66

Light distribution:-



Maintenance



Physical Details :-

Material : Aluminum
Construction : Extruded aluminum enclosure
Fixture dimensions : L 987mm x W 50mm x H 55mm
Weight : 1.8 Kgs approx.,
Mounting type : Surface mount

Protections :-

Output Over voltage /
Under voltage protected : Provided
Output Over current and
Short circuit : Provided

Applications : Outdoor & Commercial lighting

* On all electrical parameters (+/-10%) tolerance to be considered

On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice



VER 4.26