



FortuneArrrt LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearrt.com

Bulk head Technical Specification

Product Details :-

Code : LBH1010
Model : Bulk Head

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 10 Watt
Power factor : > 0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver Efficiency : > 85%

Light Data :-

LED Type : SMD LED, LM80 Certified
LED efficacy : >120lm/W
System efficacy : >75lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI : Typical 70
Diffuser : PC Diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0 °C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP65

Physical Details :-

Material : Polycarbonate casing
Fixture Dimensions : L 260mm x H 160mm
Suitable fixing : Surface mount

Applications : Indoor & Commercial



0
Maintenance



ZERO
Mercury

* On all electrical parameters (+/-10%) tolerance to be considered

* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

VER2.22