



Product Details :-

Code : LWG0536S5
Model : Non flame proof Mini well glass

Electrical Data :-

Working voltage range : 100 - 277 VAC
Input voltage : 220 - 240 VAC
Power : 36W
Power factor : > 0.95
Frequency : 50Hz
THD : < 15%
Driver : Constant current active Powerfactor corrected
Driver registration No : BIS-IS15885-2-13:2012 R-63000353 IS 16104:2012
Driver Efficiency : > 85%


Light Data :-

LED Type : SMD LED, LM80 Certified
System efficacy : >130lm/W
Beam angle : 120°
CCT range : 2700 - 6500K
CRI - Ra : Typical 70
Diffuser : Polycarbonate Diffuser
LED Life time : 50,000 hours

Environmental :-

Working temperature : 0 °C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10°C to + 85 °C
IP rating : IP65

Light distribution :-



Physical Details :-


Material : LM6 Grade aluminum or higher grade
Construction : Pressure die cast aluminum enclosure
Fixture Dimensions : Dia 140mm x H 110mm
Weight : 0.6 Kgs appr.,
Suitable fixing : Surface / Ceiling mount

Protections :-

Output Over voltage / Under voltage protected : Provided
Output Over current and Short circuit : Provided
Surge protection : With stand upto 4KV

Applications : Indoor, Outdoor & Industrial

AAI Curve :-



* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

* On all electrical parameters (+/-10%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

