



**Product Details :-**

Code : LCH10R/8  
Model : Haging Cob light

**Electrical Data :-**

Working voltage range : 100 - 277 VAC  
Input voltage : 220 - 240 VAC  
Power : 10Watt  
Power factor : > 0.9  
Frequency : 50Hz  
THD : < 15%  
Driver : Constant current active  
Powerfactor corrected  
Driver Efficiency : > 85%


**Light Data :-**

LED Type : COB, LM80 Certified  
System efficacy : >80lm/W  
Beam angle : 36°  
CCT range : 2700-6500K  
CRI(Ra) : Typical 70  
Secondary optics : Polycarbonate LENS  
LED Life time : 50,000 hours

**Environmental :-**

Working temperature : 0°C to + 55 °C  
Working humidity : 10 to 90% RH  
Storage temperature : -10°C to + 85 °C  
IP rating : IP20

**Light distribution :**




**Physical Details :-**

Material : Extruded aluminum enclosure  
Product finish : Black powder coated  
Fixture Dimensions : Dia 50mm x H 125mm  
Suitable mounting : Suspencion/Hanging

**Applications : Indoor,Outdoor & Commercial lighting**

**AAI Curve :**



\* On all electrical parameters (+/-10%) tolerance to be considered

\* On all mechanical dimensions & weight (+/-5%) tolerance to be considered

Note : The above specification are subjected to change without prior notice

