



FortuneArtrt LED Lighting Pvt Ltd.,

WQ : Survey no:509/1/2, Apparel Export park,

Gundlapochampally, Hyderabad - 500014

Web : www.fortunearttrt.com

Product Technical specification

FA-F/DD-PS 1649

Product Details :-

Code : HLDRS70610
Model : COB light - HLD series

Electrical Data :-

Working voltage range : 100 - 277VAC
Input voltage : 220 - 240VAC
Power : 10 Watt
Power factor : >0.9
Frequency : 50Hz
THD : < 15%
Driver : Constant current active
Powerfactor corrected
Driver efficiency : > 85%



0
Maintenance

50%
ENERGY
SAVING

ZERO
Mercury

Light Data :-

LED Type : COB, LM80 Certified
System efficacy : >70lm/W
Beam angle : 42 Deg
CCT range : 2700 - 6500K
CRI(Ra) : Typical 80
Secondary optics : Polycarbonate lens
LED Life time : 50,000 hours

Physical Details :-

Material & Construction : Pressure die cast aluminum
Product finish : White color
Fixture dimensions : L 65mm x W 65mm x H 57mm
Cut out dimensions : Dia 55mm
Suitable fixing : False ceiling


Applications

: Indoor & Commercial lighting

Environmental :-

Working temperature : 0°C to + 55 °C
Working humidity : 10 to 90% RH
Storage temperature : -10 °C to + 85 °C
IP rating : IP20

Light distribution:-



Note : The above specification are subjected to change without prior notice.

* On all electrical parameters (+/-10%) tolerance to be considered

On all mechanical dimensions & weight (+/-5%) tolerance to be considered



VER2.24